



Shell length code	L (l.o.a.) mm. inch	P port to port, mm. Inch	S # (span) mm. inch	M, mm/in length for membrane elements	W weight kg. lb.	Article number
21	723	540	410	485	6	41451-21
	28.5	21.3	16	19.1	12	
22	1256.5	1073.5	940	1018.5	8	41451-22
	49.5	42.3	37	40.1	18	
23	1790	1607	1480	1552	11	41451-23
	70.5	63.3	58	61.1	24	
24	2323.5	2140.5	2000	2085.5	13	41451-24
	91.5	84.3	79	82.1	29	
25	2858	2675	2540	2620	16	41451-25
	112.5	105.3	100	103.1	35	
26	3391.5	3208.5	3070	3153.5	18	41451-26
	133.5	126.3	121	124.2	41	
27	3926.5	3743.5	3600	3688.5	21	41451-27
	154.6	147.4	142	145.2	46	
28	4461	4278	4140	4223	24	41451-28
	175.6	168.4	163	166.3	52	
29	4996	4813	4670	4758	26	41451-29
	196.7	189.5	184	187.3	58	
30	5530.5	5347.5	5200	5292.5	29	41451-30
	217.7	210.5	205	208.4	63	
31	6066	5883	5740	5828	31	41451-31
	238.8	231.6	226	229.4	69	
32	6599.5	6416.5	6270	6361.5	34	41451-32
	259.8	252.6	247	250.5	75	

Table №1 for membrane length 21" (533.4mm.).
Table №2 for membrane length 40" (1016mm.).

Shell length code	L (l.o.a.) mm. inch	P port to port, mm. Inch	S # (span) mm. inch	M, mm/in length for membranes elements (with membrane type)		W weight kg. lb.	Article number
1	1208	1025	710	1020	970	8	41450-1
	47.6	40.4	28	40.2	38.2	18	
2	2224	2041	1550	2036	1986	13	41450-2
	87.6	80.4	61	80.2	78.2	28	
3	3240	3057	2550	3052	3002	18	41450-3
	127.6	120.4	100	120.2	118.2	39	
4	4256	4073	3250	4068	4018	23	41450-4
	167.6	160.4	128	160.2	158.2	50	
5	5273	5090	4250	5085	5035	28	41450-5
	207.6	200.4	167	200.2	198.2	61	
6	6291	6108	5250	6103	6053	32	41450-6
	247.7	240.5	207	240.3	238.3	72	

Warning.

1. Never pressurize a pressure vessel that was not loaded with membrane elements.
2. Wrong manifolding may cause an excessive pressure on port what can lead to leaks.
3. Max. allowable working pressure not to exceed 450 psi. (31 bar).
4. Permeate internal pressure not to exceed 125 psi. (8.6 bar).
5. Operating temperature not to exceed 49°C (120°F).

Notes:

1. All dimensions are for reference only, not for construction unless certified.
2. * - *Item 14 & 15 are optional. Delivered upon request. Priced separately.*
3. Drawing unit: mm. (inches).
4. Saddles can be shimmed if required.
5. Do not scale drawing, may be reprinted on any paper size or copied.
6. The vessel is supplied with two strap assembly.
7. For further information please contact BEL

Item	Part number	Q-ty	Title	Material
1	41450-0	1	Body of Pressure Vessel	Glass/Epoxy
2	55410208	2	Retaining ring	316 stainless steel
3	003-400-0005	2	Base plate	Engineering plastic
4	55412360	2	Seal for base plate	EPDM
5	55412377	0-6	Disk spacer	Engineering plastic
6	As required	2	Membrane seal	EPDM
7	As required	2	Adapter	Engineering plastic
8	55412367	2	Seal for Adapter	EPDM
9	009-106-0450	2	F/C Port	316 stainless steel
10	014-100-0505	2	Seal for F/C Port	EPDM
11	006-112-1202	2	Disk for F/C Port	304 stainless steel
12	011-100-1202	2	Retaining ring	316 stainless steel
13	55412368	2	Retaining ring	316 stainless steel

-Vessel support parts -optional -

14 *	55410352	2-3	Saddle	Engineering plastic
15 *	55410246	2	Strap	316 stainless steel

BEL		TITLE	DESIGN	NAME	DATE
		BEL 4-S-450 psi.	CHECK	Yuri V.	30/07/2014
		RO PRESSURE VESSEL	APPR.	Ari A.	30/07/2014
DRAWING No.		BEL 4-S-450			REV.: 4
THIS DRAWING IS PROPERTY OF BEL GROUP LIMITED IT IS STRICTLY FORBIDDEN TO USE, COPY, REPRODUCE OR DISCLOSE ANY PART OF IT TO THIRD PARTY WITHOUT WRITTEN AUTHORIZATION.					

This drawing is an integral part of the general statement of use and technical manual